


NOTES:

1. SPECIFICATIONS SHOWN CAN BE CHANGED BY THE MANUFACTURER ONLY.
2. ALL COMPONENTS OF THE GATE TO BE COATED BLACK. OTHER COLORS AVAILABLE.
3. VERIFY POST DEPTH AND FOOTING DIMENSIONS WITH LOCAL CODES AND SITE CONDITIONS.
4. CUSTOM DIMENSIONS ARE AVAILABLE UPON REQUEST.
5. OUTSIDE LOOKING IN, GATE LATCHES ON _____ (RIGHT AS SHOWN).
6. GATE OPENINGS OVER 40' WILL REQUIRE ADDITIONAL SUPPORT.
7. OPENINGS OVER 30' REQUIRE A FIELD SPLICE AND DOUBLE TRACK (AS SHOWN). GATE OPENINGS 30' OR LESS DO NOT REQUIRE A FIELD SPLICE AND ONLY REQUIRE A SINGLE ALUMINUM TRACK AND 2 SUPPORT POSTS.

 <p>COPYRIGHT © MERCHANTS METALS ALL RIGHTS RESERVED</p> <p>Merchants Metals <i>the first name in fence solutions</i></p>	<p>SECURE TRAC CANTILEVER SLIDE GATE CURVE TOP - 2 - 4 RAILS</p>	<p>BY: J.R.</p>	<p>DWG. NO. ST CG CT 10-50WX6-8H</p>
	<p>10' TO 50' WIDE OPENING x 6' TO 8' HIGH (Nom.Dimension)</p>	<p>DATE: 20 SEPT 13</p>	<p>SCALE: AS NOTED</p>
		<p>REV: D.D</p>	