



**NOTES:**

- SPECIFICATIONS SHOWN CAN BE CHANGED BY THE MANUFACTURER ONLY.
- ALL COMPONENTS OF THE GATE TO BE COATED BLACK. OTHER COLORS AVAILABLE.
- VERIFY POST DEPTH AND FOOTING DIMENSIONS WITH LOCAL CODES AND SITE CONDITIONS.
- CUSTOM DIMENSIONS ARE AVAILABLE UPON REQUEST.
- OUTSIDE LOOKING IN, GATE LATCHES ON \_\_\_\_\_ (RIGHT AS SHOWN).
- GATE OPENINGS OVER 40' WILL REQUIRE ADDITIONAL SUPPORT.
- OPENINGS OVER 30' REQUIRE A FIELD SPLICE AND DOUBLE TRACK (AS SHOWN). GATE OPENINGS 30' OR LESS DO NOT REQUIRE A FIELD SPLICE AND ONLY REQUIRE A SINGLE ALUMINUM TRACK AND 2 SUPPORT POSTS.

OPENING	COUNTERBALANCE
INSIDE FACE OF POST TO INSIDE FACE OF POST	OUTSIDE FACE OF POST TO OUTSIDE FACE OF POST
10'-0"	6'-6"
11'-0" - 14'-0"	7'-6"
15'-0" - 22'-0"	10'-0"
23'-0" - 30'-0"	12'-0"
31'-0" - 40'-0"	16'-0"
41'-0" - 50'-0"	25'-0"
ADD 4" TO COUNTER BALANCE AND OPENING FOR OVERALL LENGTH OF GATE.	



SECURE TRAC CANTILEVER SLIDE GATE  
 KENT - 2 - 4 RAILS  
 10' TO 50' WIDE OPENING x 6' TO 8' HIGH  
 (Nom.Dimension)

BY: J.R.  
 DATE: 20 SEPT 13  
 REV: D.D

DWG. NO. ST CG KN 10-50WX6-8H  
 SCALE: AS NOTED