

NOTES:

1. SPECIFICATIONS SHOWN CAN BE CHANGED BY THE MANUFACTURER ONLY.

- 2. GATE TO HANG ON THE INSIDE OF THE FENCE LINE.
- 3. FOOTING WIDTH TO BE MIN. 4(x) SIZE OF THE POST.
- 4. POSTS AND FOOTING AS REQUIRED BY CODES AND SITE CO

CONDITIONS.		40'-0"	56'-4"	16-0		
SECURE TRAC CANTILEVER GATE	BY: DDD			DWG. NO.		
GUARDSMAN 2 - 4 RAIL MONROE	DATE: 5.13.14		,	STGMO31-40		
31' - 40' WIDE OPENING x 6' - 8' HIGH						
	REV:		SCALE:		TED	
(Nom.Dimension)				AS NOTED		

33'-0'

34'-0"

35'-0"

36'-0"

37'-0"

38'-0"

39'-0"

49'-4"

50'-4"

51'-4" 52'-4"

53'-4"

54'-4"

55'-4"

16'-0'

16'-0"

16'-0"

16'-0"

16'-0"

16'-0"

16'-0"

COPYRIGHT © MERCHANTS METALS ALL RIGHTS RESERVED	R
Merchants Metals	
the first name in fence solutions	